

Highlights of NetBeans IDE 6.9 Keyboard Shortcuts & Code Templates

Finding, Searching, and Replacing

^ ⌘ G	Search Word at Insert Point
⌘ G	Find Next / Previous in File
⌘ R	Find and Replace in File
^ F7	Find Usages
⇧ ⌘ F / H	Find / Replace in Projects
^ ⇧ U	Find Usages Results
^ ⇧ H	Toggle Search Result Highlights
^ R	Rename
⌘ U, then U	Convert Selection to Uppercase
⌘ U, then L	Convert Selection to Lowercase
⌘ U, then S	Toggle Case of Selection
⇧ ⌘ V	Paste Formatted
⌘ I	Jump to Quick Search Field

Navigating through Source Code

⌘ O / ^ ⇧ O	Go to Type / File
⇧ ⌘ T	Go to JUnit Test
⇧ ⌘ B	Go to Source
⌘ B	Go to Declaration
^ G	Go to Line
⇧ ⌘ M	Toggle Bookmark
⇧ ⌘ . / ,	Next / Previous Bookmark
⇧ ⌘ 1 / 2	Select in Projects / Files
⌘ [Move Caret to Matching Bracket
^ Q	Go To Last Edit Location

Coding in Java

^ I	Generate Code
⇧ ⌘ I	Fix Imports
^ ⇧ I	Fix Import for Selected Class
^ ⇧ F	Format Selection
^ ⇧ ← / → / ↑ / ↓	Select Left / Right / Up / Down
^ ⇧ ↑ / ↓	Copy Selection Up / Down

⌘ F12	Inspect Members / Hierarchy
⌘ /	Add / Remove Comment Lines
⌘ E	Delete Current Line

Coding in C/C++

^ ⇧ G	Go to Declaration
⌘ F9	Evaluate Expression

Coding in Ruby

⇧ ⌘ A	Jump Rails Action > View
^ ⇧ . / ,	Select Next/Previous Element
⇧ ⌘ Space	Display Documentation
⇧ ⌘ T	Jump from Test File to File

Compiling, Testing, and Running

⇧ ⌘ U	Create JUnit Test
⇧ ⌘ T	Go to JUnit Test
^ F6 / ⌘ F6	Run JUnit Test on Project / File
F6 / ⇧ F6	Run Main Project / File
⇧ ⌘ F6	Debug Test File

Opening and Toggling between Views

⌘ `	Go to Previous Document
⇧ Esc	Maximize / Minimize Window (Toggle)
⌘ W	Close Currently Selected Window
⇧ ⌘ F4	Close all Windows
^ ⇧ D	Undock / Redock Window (Toggle)

Debugging

⇧ ⌘ F5	Debug Selected File
⇧ ⌘ F6	Debug Test File (JUnit)
F5	Continue Debugger Session
⇧ F5	Finish Debugger Session

F4	Run to Cursor Location in File
F7 / F8	Step Into / Over
⌘ F7	Step Out
^ ⇧ / ↓	Go to Called / Calling Method
⌘ F7	Evaluate Expression
⌘ F8	Toggle Breakpoint
⇧ ⌘ F8	New Breakpoint
⇧ ⌘ F7	New Watch

Notes:

- **^** represents ctrl
- Press fn to use function keys (e.g., F5, F6, F8)

Java Editor Code Templates

When typing in the Source Editor, generate the text in the right-column below by typing the abbreviation that is listed in the left-column and then pressing Tab.

En	Enumeration
Ex	Exception
Ob	Object
Psf	public static final
Psfb	public static final boolean
Psfi	public static final int
Psfs	public static final String
St	String
ab	abstract
as	assert true;
bcom	/**/
bo	boolean
br	break;
ca	catch (

Highlights of NetBeans IDE 6.9 Keyboard Shortcuts & Code Templates

cl	class
cn	continue
db	double
df	default:
dowhile	do { } while (<i>condition</i>);
eq	equals
ex	extends
fa	false
fcom	// <editor-fold></editor-fold>
fi	final
fl	float
forc	for (Iterator <i>it</i> = <i>collection.iterator()</i> ; <i>it.hasNext()</i> ;) { <i>Object elem</i> = (<i>Object</i>) <i>it.next()</i> ; }
fore	for (<i>Object elem</i> : <i>iterable</i>) { }
fori	for (int <i>i</i> = 0; <i>i</i> < <i>arr.length</i> ; <i>i</i> ++) {}
forl	for (int <i>i</i> = 0; <i>i</i> < <i>lst.size()</i> ; <i>i</i> ++) { <i>Object object</i> = <i>lst.get(i)</i> ; } }
forst	for (StringTokenizer <i>st</i> = new StringTokenizer(""); <i>st.hasMoreTokens()</i> ;) }
forv	for (int <i>i</i> = 0; <i>i</i> < <i>vct.size()</i> ; <i>i</i> ++) { <i>Object object</i> = <i>vct.elementAt(i)</i> ; }
fy	finally { }
ie	interface
ifelse	if (<i>condition</i>) {} else { }
iff	if (<i>exp</i>) {}
im	implements
inst	if (<i>exp instanceof Object</i>) { <i>Object obj</i> = (<i>Object</i>) <i>exp</i> ; }
iof	instanceof
ir	import
le	length
na	native
newo	<i>Object name</i> = new <i>Object(args)</i> ;
pe	protected
pr	private
psf	private static final

psfb	private static final boolean
psfi	private static final int
psfs	private static final String
pst	printStackTrace();
psvm	public static void main(String[] args) { }
pu	public
re	return
runn	Runnable runnable = new Runnable() { public void run() {} };
serr	System.err.println ("");
sh	short
sout	System.out.println ("");
soutv	System.out.println("Object = " + <i>Object</i>);
st	static
su	super
sw	switch (var) { case val: break; default: throw new AssertionError(); }
sy	synchronized
tds	Thread.dumpStack();
th	throws
tr	transient
trycatch	try { catch (Exception <i>e</i>) {} }
tw	throw
twnew	throw new
vo	volatile
wh	while (
whileit	while (<i>it.hasNext()</i>) { <i>Object elem</i> = (<i>Object</i>) <i>it.next()</i> ; }
whilen	while (<i>en.hasMoreElements()</i>) { <i>Object elem</i> = (<i>Object</i>) <i>en.nextElement()</i> ; }
whilexp	while (<i>exp</i>) {}

JSP Editor Code Templates

ag	application.getAttribute(" ")
ap	application.putAttribute(" ",)
ar	application.removeAttribute(" ")
cfgi	config.getInitParameter(" ")
jspf	<jsp:forward page=" "/>
jspxg	<jsp:getProperty name=" " property=" " />
jspfi	<jsp:include page=" "/>
jsppl	<jsp:plugin type=" " code="" codebase=" "></jsp:plugin>
jspss	<jsp:setProperty name=" " property=" "/>
jspu	<jsp:useBean id=" " type=" "/>
oup	out.print(" ")
oupl	out.println(" ")
pcg	pageContext.getAttribute(" ")
pcgn	pageContext.getAttributeNamesInScope(" ")
pcgs	pageContext.getAttributeScope(" ")
pcr	pageContext.removeAttribute(" ")
pcs	pageContext.setAttribute(" ",)
pg	<%@page %>
pga	<%@page autoFlush="false"%>
pgb	<%@page buffer=" kb"%>
pgc	<%@page contentType=" "%">
pgerr	<%@page errorPage=" "%">
pgex	<%@page extends=" "%">
pgie	<%@page isErrorPage="true"%>
pgim	<%@page import=" "%">
pgin	<%@page info=" "%">
pgit	<%@page isThreadSafe="false"%>
pgl	<%@page language="java"%>
pgs	<%@page session="false"%>
rg	request.getParameter(" ")
sg	session.getAttribute(" ")
sp	session.setAttribute(" ",)
sr	session.removeAttribute(" ")
tglb	<%@taglib uri=" "%">